

## ABOUT THAT FIBROUS MATTER

The 12X is designed for entry-level tree care companies, municipalities, rental yards, and utility right-of-way crews that need portability as well as durability to compress and process volumes of wet, leafy, limby, viney, and stringy material including palm fronds.

# **SLIMMED DOWN, YET ROBUST**

The 12X was built to be light and nimble, but it's not lacking in power. The 14-foot length and 6-foot 2-inch width means this machine is compact, and at only 4,700 lbs, it can easily be towed by a regular pickup truck.

#### CHIP CHUP

The 12X will process tree trimmings and brush quickly and efficiently. The single 15 ¾" diameter by 21-3/8" feed wheel will pull in and compress stubborn branches, especially with the aid of an optional infeed lift cylinder. The 20" diameter 18-3/4" wide drum spins two knives at nearly 2,000 rpm to chip quickly.

# **EASY TO SERVICE. PLEASURE TO RUN**

Spend more time chipping with the 12X. With only two knives to maintain and few points requiring grease, the machine's daily maintenance routine should only take minutes. The 12X is also designed to be easy to operate and intuitive controls mean rental customers will feel like seasoned professionals after only a few minutes of run time.



Sydney • Brisbane • Canberra • Melbourne • Perth 1800 681 733

**Hand-Fed Chippers** • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

## **SPECIFICATIONS**

MEASUREMENTS	TOWABLE	
Length:	16' 2"	492.8 cm
Width:	6' 7"	200.7 cm
Height:	8' 1"	246.4 cm
Weight:	4,700 lbs.	2,131.8 kg
Engines:	84 HP Kubota Engine	
Fuel Tank:	24.5 gallon	92.7 L
Hydraulic Tank:	12 gallon	45.4 L

#### **UNDERCARRIAGES**

Towable: (1) 6,000 pound axle with (2) ST225/75R 15" (38.1cm) tires mounted on 6-bolt white modular rims

#### **DIMENSIONS**

Capacity:	12"	30.48 cm
Opening:	12.06" high x 18.75" wide	30.63 cm x 41.75 cm wide
Drum:	20" dia. x 18.75" wide	50.8 cm dia. x 47.6 cm wide
RPM:	Approximately 1,930 RPM	

Hitch: 2-1/2" pintle hitch

Discharge: 360° manual swivel with 12" (30.5 cm) adjustable chip deflector

Feed System: Pivot arm feed system with (2) 17" (43.2 cm) adjustable down pressure springs, (1) 15-3/4" diameter x 21-9/16" wide feed wheel (40.0 cm x 54.8 cm) powered by (1) 48 CID hydraulic motor

Frame: 4" channel main frame (10.16 cm)



### **COMMITTED TO QUALITY & SERVICE**

#### The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipper — regardless the age, hours, or warranty status — the Bandit Backbone is here to support you.

#### **We Are Here to Support You**

Bandit are a member of the EEA Group with branches across NSW, ACT, VIC, QLD and WA. Our team put the customer and their business first. Plus we have an experienced parts and service department supporting you and our dealers.



### INTIMIDATOR™ 12X FEATURES

- Rope/Line Shear Device (standard)
  Provides an improved chance that rope or lines inadvertently entering the chipper may be cut
- Last Chance Cables (standard)
  Stops/reverses the feed wheel when pulled in case of an emergency
- Operator Safety Control Bar (standard)
  Wraps around 3 sides of the infeed chute & controls the direction of feed wheels
- Wood Pusher Paddle (standard)
  Used to feed small wood debris into the chipper
- Chipper Hood Pin w/Padlock (standard)
  Prevents unauthorized access to the disc or drum
- Chipper Hood Engine Disable Plug (standard)
  Prevents engine from being started without the hood pin in place
- Hydraulic Bottom Bump Bar (option)
  Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels

Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments